RAILING FRAME COMPONENTS WITH 400 LBS. (182 KG) PRESTRESS PER CABLE

RAILING	CARBON STEEL		STAINLESS STEEL
	A53, Grade B, Fy=35 ksi or	A572,	There is presently no commercially
O THE PERSON OF	A501, Grade B, Fy=36 ksi	Grade 55, Fy=55 ksi	available stainless steel suitable for
**************************************	(Pipe)	(Round Bar)	use with this frame. Consider 1-1/2"
			pipe for which there is a commonly
TANAN MARKATANA			available stainless steel material (see
	,		drawing D22).
1-1/4" Pipe x 36-1/2" High without Bottom Rail			· ·
Anchor (End) Post		1.66" Dia. round bar	
	Hadden Park	*(See note)	
Intermediate Post	1-1/4" Schedule 40 pipe	, , , , , , , , , , , , , , , , , , ,	
Top Railat		THE STATE OF THE S	
Anchor Post		1.66" Dia. round bar	THE PROPERTY OF THE PROPERTY O
		*(See note)	
Top Rail Elsewhere	1-1/4" Schedule 40 pipe	rosses especial de la company	

^{*}Note: Material specified for these posts may not be readily available or may be very expensive. Consider using a design with a bottom rail for which there is a pipe that is commonly available (see drawing D25).