Inside-of-Post to Outside-of-Post Mount

Wood Posts

Straight Cable Runs and Cable Runs through One Corner

Deck 1 has dedicated end posts, but the posts next to the house are too close to access the back side of the posts. Run #1 is outside to outside, so it will take a Series 262 kit. However, for Runs #2 and #3, you will attach to the inside of the posts next to the house and run through the post at the other end.

Deck 2 has shared corner posts, but the posts next to the house are placed such that the back side of the posts are accessible, so for Runs #2 and #3, you will attach to the inside of the corner posts and run through the post next to the house.

Deck 3 illustrates how the 601 series can also be used to go around a single corner up to 90°.

Applicable kit is the 601 Series

The tensioning device is a 31/2" long Invisiware Receiver, which installs through the wood post on one end. A Push-Lock Lag is lagged into the other end.



Tools needed for 601 Series:

5/32 drill bit if 1/8" cable, 7/32 if 3/16"

29/64 drill bit for Receiver installation

3/16 Hex wrench for tensioning Receiver

9/32 drill bit for Push-Lock Lag installation

Series 601 Kits			
Cable	1/8" cable	3/16" cable	
Length	PART NO.	PART NO.	
5′	60105	60105-6	
10′	60110	60110-6	
15′	60115	60115-6	
20′	60120	60120-6	
25′	60125	60125-6	
30′	60130	60130-6	
40′	60140	60140-6	

Cable	1/8" cable	3/16" cable
Length	PART NO.	PART NO.
5′	60105	60105-6
10′	60110	60110-6
15′	60115	60115-6
20′	60120	60120-6
25′	60125	60125-6
30′	60130	60130-6
40′	60140	60140-6
50′	60150	60150-6

7/16 wrench for tightening Push-Lock Lag Cable cutting tool If using Post Protector Tubes, 1/4 drill bit







For Post Protector Tubes, see Tools and Essentials section.



American Structures & Design Inc. - WA 218 Stewart Rd. SE, Pacific, WA 98047 P: 253-833-4343 F: 253-833-4545 AmericanStructures.com

American Structures & Design Inc. - OR 13444 NE Jarrett St. Portland, OR 97230 P: 971-645-4201 F: 971-645-4212

